

Super Duty Disc Harrow KLR GAC245



Renovate a pasture, incorporate heavy residue, or work the toughest construction site;
Spacing between the discs 245 mm .

MODEL	Nº OF DISCS	WEIGHT	WORK WIDTH	REQUIRED POWER (cv.)
GAC245 1424	14x24"	1.254 kg	1.750 mm	70-80
GAC245 1624	16x24"	1.339 kg	2.020 mm	80-90
GAC245 1824	18x24"	1.407 kg	2.250 mm	95-105
GAC245 2024	20x24"	1.477 kg	2.500mm	100-120
GAC245 2224	22x24"	1.760 kg	2.750 mm	120-130
GAC245 2424	24x24"	1.880 kg	3.000mm	140-160
GACP245 2824	28x24"	2.570 kg	3.250mm	160-175
GAC245 1426	14x26"	1.303 kg	1.750 mm	70-80
GAC245 1626	16x26"	1.395 kg	2.020 mm	80-90
GAC245 1826	18x26"	1.470 kg	2.250 mm	95-105
GAC245 2026	20x26"	1.547 kg	2.500mm	100-120
GAC245 2226	22x26"	1.760 kg	2.750 mm	120-130
GAC245 2426	24x26"	1.880 kg	3.000mm	140-160
GACP245 2826	28x26"	2.570 kg	3.250mm	160-175
GACP245 3226	32x26"	2.780 kg	3.000mm	140-160
GACP245 3626	36x26"	3.000 kg	3.250mm	160-175