

Super Duty Disc Harrow KLR GAC270



Renovate a pasture, incorporate heavy residue, or work the toughest construction site;
Spacing between the discs 270 mm.

MODEL	N° OF DISCS	WEIGHT	WORK WIDTH	REQUIRED POWER (cv.)
GAC270 1426	14x26"	1.326 kg	1.890mm	80-90
GAC270 1626	16x26"	1.418 kg	2.160mm	95-105
GAC270 1826	18x26"	1.497 kg	2.430 mm	110-120
GAC270 2026	20x26"	1.710 kg	2.700 mm	120-140
GAC270 2426	24x26"	1.880 kg	3.240 mm	145-160
GACP270 2826	28x26"	2.630 kg	3.780 mm	170-180
GACP270 3226	32x26"	2.790 kg	4.320 mm	210-220
GACP270 3626	36x26"	2.970 kg	4.860 mm	230-250
GACP270 4026	40x26"	3.220 kg	5.400 mm	250-280
GAC270 1428	14x28"	1.365 kg	1.890mm	80-90
GAC270 1628	16x28"	1.466 kg	2.160mm	95-105
GAC270 1828	18x28"	1.551 kg	2.430 mm	110-120
GAC270 2028	20x28"	1.710 kg	2.700 mm	120-140
GAC270 2428	24x28"	1.880 kg	3.240 mm	145-160
GACP270 2828	28x28"	2.630 kg	3.780 mm	170-180
GACP 270 3228	32x28"	2.790 kg	4.320 mm	210-220
GACP270 3628	36x28"	2.970 kg	4.860 mm	230-250
GACP270 4028	40x28"	3.220 kg	5.400 mm	250-280